

## Multi-Stage Duplex (MSD™) Pump

### Operating Parameters

Model *	MSD-350	
Liquid	Seawater, Brackish water, Fresh Water	
Pump Operating Ambient Temp	33 - 158 °F	0.6 - 70.0 °C
Maximum Storage Temp	185 °F	85.0 °C
Pump Operating Flow Range**	771-2157 gpm	175-490 m³/h
Maximum Operating Pressure	1200 psi	83 bar
Maximum Inlet Pressure	150 psi	10.3 bar
Maximum High Inlet Pressure	1100 psi	75.8 bar
Nominal Vibration	≤7.1mm/sec RMS	≤0.28"/sec RMS
Nominal Sound	<85 bBA	
Filtration Requirement	20 microns	

\* Subject to international patent applications

\*\* Range may vary

### Performance

Peak Efficiency	Contact FEDCO for specific performance data
-----------------	---

### Materials

Shaft	Super Duplex SS S32750 ASTM A276/479
Stage Bolting	316 SS S31600 ASTM A193/A320/F593
Inlet/ Discharge	Super Duplex SS S32760 ASTM A995 6A
Impellers/ Diffusers	Super Duplex SS S32760 ASTM A995 6A
Motor Adapter	Anodized 713 aluminum A07130 ASTM ZC81A
Motor Coupling	Flexible Disc-FNC Treated Carbon Steel S45C ASTM 1045
Coupling Guard	316L S31603 ASTM A276/479
Pump Leveling Foot	Carbon Steel - A36 Painted ASTM A570/A
Bearing Drain Line	Super Duplex SS S32750 ASTM A-789
Mechanical Seal	316 Carbon Silicon Carbide Buna N FITS ISO DIN/ANSI TYPE 2100
O-Rings	Buna N®
Optional Baseplate	Carbon Steel - A36 Painted ASTM A570/A
Crating/Packaging	Export-Wood

### Options

Inlet placement available in 90° increments.

High pressure inlet and seal package available

### Outline

Each MSD model is custom designed to specific customer requirements.

### Packaging/ Crating

Protective Covers	Standard
Export Crating	Standard
Additional Shipping Options	Available per customer requirements
Unit Weight (Dry)	Contact FEDCO for design weight

### Hydraulic Design

Pump	Horizontal multi-stage centrifugal pump with barrel flanged joint construction.
------	---

### Fittings

Pipe Joints	Feed Inlet 8" Cut Groove Feed Outlet 8" Cut Groove
-------------	---

### Drive

Motor	Available per customer specific requirements NEMA Frame Standard, IEC Available
-------	--

### Bearings

Thrust	FEDCO Water Bearing™ Product Lubricated
--------	--

Cooling	Product fluid
Lubrication	Product fluid

### Testing and Inspection

Performance Test	Standard
------------------	----------

Hydrostatic Test	Standard
------------------	----------

Visual/ Dimension Check	Optional
Sound Test	Optional
Vibration Test	Optional
Witness Test	Optional
Certified Test Data	Optional
Material Certificates	Optional

\* General Code Groups, Associations, Laboratories, and Approval Bodies include the American Society for Testing and Materials (ASTM), the International Organization for Standardization (ISO), and the NSF International.



NOTE: All numeric values are based on performance norms. Specific performance data is included with each individual unit. FEDCO reserves the right to make specification changes at any time without prior notice. Please contact your FEDCO representative for information. email: sales@fedco-usa.com